



## CANDY

The La Nordica CANDY is a stylish radiant heat wood burning free standing fireplace made entirely of very high thermic yield cast iron. The exterior entirely coated in an enamel finish. The firebox is cast iron with post combustion system. The CANDY has an average power output of 7.4 kW, peak average of 8.7kW and meets the latest “benchmark” German certification standards as well as Australian standards. Highly efficient radiant wood burning fireplace.

### Dimensions

#### Overall

Width	404mm
Height	890mm
Depth	397mm
Weight	84kg

#### Firebox Opening

Width	233mm
Height	315mm

#### Firebox Internal Dimensions

Width	330mm
Height	356mm
Depth	215mm

#### Flue Specifications

Diameter, adapter inc.	150mm
Centre of flue to rear of fire	202mm

### Special Features

- Nominal output: 7.4kW
- Window Height 390mm, Width 215mm
- Large viewing window (CGC)
- Firebox in G20 high thermal yield cast iron
- Entirely cast iron enamelled stove (RDT)
- Enamelled cast iron exterior
- Post combustion system (PCS)
- Particle emissions: 1.2g/kg
- Efficiency: 65% (AS/NZS4012/4013), 85.1% (EUROPEAN)\*
- Wood consumption: 1.5kg/hr @ medium burn rate





## Clearances

### Combustible Rear Wall

Rear Clearance	575mm
Rear Clearance with Shield	250mm
Side Clearances	775mm

Front Hearth	300mm
Min. Hearth Width	635mm

### Combustible Corner Wall

Corner Clearance	700mm
Corner Clearance with Shield	400mm

To achieve stated clearances to heat sensitive materials one 900mm length of heat shield must be fitted to the flue above the fire in accordance to AS/NZS 2918:2018. This can include half-moon shields or decromesh approved kits. With the use of a heat shield in accordance to AS/NZS 2918:2018 you can reduce rear clearances to 173mm for rear wall and 210mm for corner wall.

## Certification

- AS/NZS 4012/4013 (2014) (Australia)
- 15a B-VG (Austria)
- BlmSchV (Germany)
- Flamme VERTE Le Label du chauffage au bois (France)
- Certificazione aria PULITA 4 Stars, AE5-P-048 (Italy)

**\*IMPORTANT NOTE:** According to the AS/NZS 4012/4013 efficiency, 4 logs (4.3Kg) were used for testing. The manufacturers recommendation is 2 logs (2.2Kg) which will result in higher efficiency and less wood used while achieving same heat output.

## CGC Clean Glass Control

A System to preheated air which removes any deposits from forming on the hearth door glass.

## PCS Post Combustion System

The combustion system developed by La Nordica allows, due to a secondary/tertiary air system, a post combustion which significantly reduces emissions.

## RDT Resistant Door at the Time

La Nordica-Extraflame appliances doors are manufactured in high quality cast iron.

